

Outdoor Linear Light

- To draw the contour of large-scale architecture like building, elevated freeway, bridge, curtain wall etc.
- Narrow section, covered by UV-resistant acrylic, Extremely uniform light effect, soft and uniform, consistent light
- Fully sealed and waterproof design with Germany adhesive.

Basic Specification

Product name	LED Linear Light
Type	Facade Illumination
Model No.	HTA3545A
Body Material	Aluminum
Cover	PMMA (Acrylic)
Mounting:	Surface mount
IP Protection	IP65
Dimensions	W 35 x H45 x L1000 MM
Net Weight (1 pcs)	0.860 kg

Electrical Specification

Power Consumption	12W
Input Voltage	DC24V/DC48V
Power Factor	≥0.95
Control Method	On-Off/DMX512/RDM/SPI


Lighting Specification

Color Temperature	2200-6500K/RGB/RGBW
CRI	80 @4000K
LED Chip	OSRAM/EPISTAR/SANAN
LED Qty	48/60 pcs
Luminous Flux	600 Lm @4000K
Beam Angle	150°
LED Lifespan	≥50000 hr @Ta 40 °C
Working Temperature	-25 °C ~ 58 °C




IP65 Protect Grade	V-0 Fireproof Grade	IK10 Impact Test	Anti-UV	Salt Spray	III
-----------------------	------------------------	---------------------	---------	------------	-----

Product Drawing



1000/800/600/500/300/200 MM

Spatial Distribution Curves



The appearance and color of all products listed in this data sheet are for reference only.
Glow reserves the right to modify specifications and/or discontinue any product at any time without prior notice.